

ZHEJIANG HANGCHA IMP. & EXP. CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com



Facebook



IS014001:2015

YouTube



WeChat







Forklift" App







 ${\sf HANGCHA\,GROUP\,CO.,LTD.}\ reserves\ the\ right\ to\ make\ any\ changes\ without\ notice\ concerning$ colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



A series pallet truck mini range III

with capacities of 1,500/2,000kg



A series pallet truck mini range III



High Performance

- / Rated capacity 1500-2000kg, meet the needs of the majority of customers.
- / Powered by traction motor not only has good acceleration and perfect performance, but also low heat.
- / Regenerative braking for battery recovery during travel speed reduction, anti-slope on gradient.
- / All key parts such as tiller, switches, connectors, battery indicator and hour meter all adopt the famous brand.

/ Make the operator feel comfortable, all the operation

/ Optimized designing structure to offer a good visibility

/ The compact body and semicircular design provide an

walking upright greatly increases the convenience in

/ Standard fork height 80mm, equipped the guide device easy to get in pallets (including sealing pallets).

ideal operation in limited space, and the ability of

/ Built-in charger and maintenance free gel battery

can be completed by one hand.

and easy entrance of the pallet.

adopted to provide convenient usage.

/ Side battery change is standard feature.

Safety

- / Three braking system of regenerative braking, reverse current braking, parking brake, insures the safe opera-
- / Anti-slope on gradient can keep the safety.
- / The emergency button on the tiller head can effectively
- / The standard equipped electronic lifting limitation and more energy saving.
- avoid the harm to the driver.
- protect the pump motor from damaging dramatically

Maintenance

- / Built-in charger and maintenance free gel battery, you don't need to worry about them.
- / Integrated battery indicator, hour meter and self-diagnostic instrument.
- / Full opened hood, easy accessibility of all components, is easy for service.
- / All shafts installed lubricated shaft sleeve and oil cup, provide convenient maintenance and long service life.

Standard specification

- / Permanent magnet drive motor
- / Emergency switch
- / Multi-function battery indicator
- / PU wheel
- / 1150mm fork length
- / 560mm outside fork width
- / Electronic lifting limitation
- / Non-contact proximity switch
- / Horn
- / Maintenance free battery
- / Internal charger
- / Walking upright
- / Additional wheel
- / Tandem load wheel

Options

/ Different length of fork / Different width of outside fork











Reliability

Comfort

- / 5-pivot design provide longer working life.
- / Imported waterproof connectors, all wires and cables are protected, greatly improve the reliability of the electric system.
- / Top quality hydraulic power unit applied to provide low noise, low vibration, smooth lifting and landing reliable
- / Punch formed forks to provide more strength and tip guide to provide higher efficient operation.
- / Using non-contact proximity switch, improves safety and reliability.